

**PRODUCT NAME (产品名称): Flexiplas TF (柔塑性胶水)**

## MAIN APPLICATIONS 主要应用

The Flexible Plastic adhesive is a PVC base adhesive, designed for bonding flexible plastics.  
柔塑性胶水属于 PVC 树脂类胶水, 专用于粘接柔软塑料.

## SOLUBILITY 可溶性

Non-polar solvents like toluene, hexane, ethyl acetate, MEK, etc.  
易溶于非极性溶剂, 如: 甲苯, 己烷, 乙酸乙酯, 丁酮等.

## PRODUCT SPECIFICATIONS 产品技术指标

Properties (性能)	Specifications (指标)
Viscosity Brookfield, cp @ 23 °C, 20 rpm (23 °C, 20rpm 条件下的粘度, cp)	250 - 1250
Solid content, % (固含量 %)	17.5-21.5
Density, g/cc @ 20 °C (密度)	0.89 - 0.91
*Color (外观)	Transparent 透明

\* Typical value (典型值)

## STORAGE CONDITIONS 存储条件

Keep in dry place between 15 - 25 °C and be protected from heat, moisture and foreign materials.  
In this conditions the validate time is 12 months.  
存放在 15~25° C 的干燥条件, 远离热源, 火源, 湿气和其他原料的地方, 保质期 12 个月.

Designed by:



José Ramón Cerezo  
Technical Director GSA

Approved by:



Cai Ping Chen  
Technical and R&D Manager  
GYMCOL China